



Product Data Sheet

www.calumetspecialty.com

If you have questions regarding this product, please contact your Sales Representative. Customer Service and Technical Service can be reached at 1-800-437-3188.

Name	Product Code	Revised
Drakeol® 35 MIN OIL USP	PEN1440-00-C	03/17/2009

STCC 29-114-16

HazMat Name Non-Regulated

Test	Method	Typical
Viscosity, CST @ 40C	D445	67.6
Viscosity, SUS @ 100F	D2161	350.5
Gravity, API, 60°F	D4052	30.7
Specific Gravity, 60/60F	D4052	0.872
Specific Gravity @ 25/25 C	D4052	0.868
Flash Point, COC, F	D92	454
Pour Point, F	D97	-1
Color (Saybolt)	D156	+30
Solid Paraffins	USP	PASS
Readily Carbonizable	USP	PASS
Acidity	USP	PASS
Odor, USP/NF	USP/NF	PASS
FDA 21 CFR 172.878	FDA	PASS
Limit of Polycyclic Aromatic Hydrocarbons	USP	PASS
Limit of Sulfur Compounds	USP	PASS
Infrared Absorption	USP	PASS

Copyright 2008 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Typical values only represent the values one would expect if the property were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values are not based on a statistically relevant number of tests. The information in this document relates only to the named product. The user is solely responsible for all determination regarding any use and any process.