



# Product Data Sheet

[www.calumetspecialty.com](http://www.calumetspecialty.com)

If you have questions regarding this product, please contact your Sales Representative. Customer Service and Technical Service can be reached at 1-800-437-3188.

<b>Name</b>	<b>Product Code</b>	<b>Revised</b>
Drakeol® 9 LT MIN OIL NF	PEN1540-00-C	06/01/2009

**STCC** 29-114-16

**HazMat Name** Non-Regulated

Test	Method	Typical
Viscosity, CST @ 40C	D445	15.7
Viscosity, SUS @ 100F	D2161	85.6
Gravity, API, 60°F	D4052	34.2
Specific Gravity, 60/60F	D4052	0.854
Specific Gravity @ 25/25 C	D4052	0.850
Flash Point, COC, F	D92	382
Color (Saybolt)	D156	+30
Solid Paraffins	USP	PASS
Readily Carbonizable	USP	PASS
Acidity	USP	PASS
Odor, USP/NF	USP/NF	PASS
FDA 21 CFR 172.878	FDA	PASS
Limit of Polycyclic Aromatic Hydrocarbons	USP	PASS
Limit of Sulfur Compounds	USP	PASS
Infrared Absorption	USP	PASS

Copyright 2008 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Typical values only represent the values one would expect if the property were tested in our laboratories with our test methods on the specified date. Some product properties are not frequently measured, and accordingly typical values are not based on a statistically relevant number of tests. The information in this document relates only to the named product. The user is solely responsible for all determination regarding any use and any process.